



PT - 88800

All-in-one POS system



- ✓ Fanless
- ✓ Modern stylish design
- ✓ 15 inch P-CAP touch screen display
- ✓ 80 mm fast, reliable thermal printer
- ✓ Customer display
- ✓ Easy maintenance and service



The new PT - 88800 POS system is a TRUE All-in-One POS system. In a single housing PT - 88800 incorporates a POS system, fast reliable thermalprinter and customer display. Everything is packed in a sleek modern design that is suitable for most applications. Powerful J1900 provides possibility to use the most demanding applications today.

PT - 88800 true all-in-one POS is made for businesses that demand exceptional value along with the reliability and performance they can rely on.



SLEEK DESIGN



TOUCH-SCREEN DISPLAY



CUSTOMER DISPLAY



PRINTER

ALL-IN-ONE DESIGN

METAL HOUSING



MAGNETIC CARD READER



PT - 88800

All-in-one POS system



Specification

| | | |
|-------------------------------|---|---|
| CPU | INTEL® Bay Trail CPU Celeron J1900 Quad Core Processor, 2GHz, 10W | |
| Chipset | Adopt® Intel Baytrail-D chipset Integrated Intel HD Graphics | |
| RAM | 4 GB (expandable up to 8 GB) SO-DIMM DDR3L 1333 MHz | |
| Expansion Slot | 1x Mini PCIe slot | |
| SATA | SATA V2.0/3.0 Data transfer rates up to 3.0/6.0 Gb/s | |
| Disk Drive | 64 GB SSD (expandable) | |
| Audio | High Definition Audio Device | |
| Ethernet LAN | Realtek GBE Family 10/100/1000 Mb/s | |
| Interfaces | LAN USB Drawer Serial Display | 1x RJ-45 port 6x (2x Back USB 3.0 + 2x Back 2.0 + 2 Side USB 2.0) ports 1x RJ-11 port 3x RS-232 port 1x VGA port, supports extended desktop |
| Display size | 15" (1024x768) LCD with Projected Capacitive Touch | |
| OS Compliant | Microsoft Embedded 8.1 Industry Pro Retail (64-bit) Microsoft Windows 10 IoT Ent LTSB (64-bit) | |
| Printer | SII - (CAPD 347) : 88800 | |
| Printing method | thermal line dot printing | |
| Number of dots/line | 576 | |
| Resolution | 8 dots/mm | |
| Paper roll size | 80 mm, max. Ø 60 mm | |
| Printing width | 72 mm | |
| Max. speed | 200 mm/sec. | |
| Cutter | full cut or partial cut | |
| Printer head life | 100 million impulses | |
| Abrasion resistance | 100 km | |
| Cutter life | 1 000 000 cuts | |
| Customer display | Blue LCD 2 x 20 characters | |
| Magnetic stripe reader | integrated (optional) | |
| Operating Temperature | 0°C to +48°C | |
| Dimensions | Dimensions : 354 (W) x 368 (D) x 119 (H) mm – 88800 | |
| Fiscal Module | Probus fmPOS (optional) | |
| Dallas Key | optional | |
| Factory options | resistive touch panel | |



www.probus.tech



+61 (0)2 84048040



info@probus.tech / sales@probus.tech

